

# NSK NU 211 EW cylindrical roller bearings

Various types and sizes 35 mm d to accommodate your 45 mm d1 NSK NU 211 EW cylindrical roller bearings requirements. 205 mm a

d	35 mm
d1	45 mm
a	205 mm
b	60 mm
c	25 mm
g	39 mm
h	60 mm
h1	107 mm
l	85 mm
l1	94 mm
l2	151 mm
l3	107
m	170 mm
m1	160 mm
m3	130 mm
n1	34 mm
m2	188 mm
n2	44 mm
diameter dowel pins	5 mm
u	15 mm
v	20 mm
D	80 mm

B	9 mm
housing weight	3.1 kg
Material of Housing	grey cast
initial grease quantity	80 Volume_cmc
sealing DS	SC 510 DS
sealing LA	SC 510 LA
sealing SV	SC 510 SV
sealing TA	SC 510 TA
sealing FS	SC 307 FS
end cover EC	SC510-608EC
V-ring option	V45A
fixing bolts G	M12
recommended torque	65 Nm
Connection bolts	M12x50
maximum loads 120°	80 kN
maximum loads 150°	45 kN
maximum loads 180°	40 kN
P 0°	265 kN
P 55°	220 kN
P 90°	132 kN
P 120°	95 kN
P 150°	85 kN
P 180°	115 kN