

# NSK NU2205 ET cylindrical roller bearings

NSK NU2205 ET cylindrical roller bearings Engineering Calculator , 29 N/mm<sup>2</sup>;Static 150 N/mm<sup>2</sup> maximum p value: Manufacturing Service 55.3 mm inside diameter: . Get Your Free.

|                              |   |
|------------------------------|---|
| inside diameter:             | 55.3 mm   |
| maximum p value:             | 29 N/mm <sup>2</sup> ;Static 150 N/mm <sup>2</sup>  |
| D                            | 110 mm  |
| maximum v value:             | Dry 0.50 m/s;Periodic lubrication 1.0 m/s   |
| thickness:                   | 8 mm  |
| material specification:      | 500SP1 SL1  |
| bearing material:            | OILES 500SP1 SL1 High-Strength Brass with Embedded Solid Lubricant                                      |
| standards met:               | RoHS  |
| operating temperature range: | Periodic Lubrication -40 to +302 °F, Dry -40 to +572  |
| additional details:          | Lead Free   |
| maximum pv value:            | Periodic Lubrication 3.25 N/mm <sup>2</sup> x m/s, Dry 1.65 N/mm <sup>2</sup> x m/sPeriodic Lubrication |
| series:                      | SPW   |