

NSK NUP 208 EW cylindrical roller bearings

With over 10170 full-service stores, our NSK NUP 208 EW cylindrical roller bearings inventory is extensive and our parts are priced right. within 24 hours. This helps you maximize your productivity by saving time 161,925 Outer Diameter (mm) and your hard-earned 76.2×161.925×53.975 Size (mm) dollars.

Size (mm)	76.2×161.925×53.975
Bore Diameter (mm)	76,2
Outer Diameter (mm)	161,925
Width (mm)	53,975
d	76,2 mm
D	161,925 mm
T	53,975 mm
B	55,1 mm
C	42,862 mm
ra1 max.	3,3 mm
a	40,7 mm
r min.	3,5 mm
r1 min.	3,3 mm
Da	141 mm
db	92 mm
ra max.	3,5 mm
da	99 mm
Db	154 mm
Weight	5,41 Kg
Basic dynamic load rating (C)	325 kN

Basic static load rating (C0)	480 kN
(Grease) Lubrication Speed	2200 r/min
(Oil) Lubrication Speed	3000 r/min
Calculation factor (e)	0,4
Calculation factor (Y0)	0,82
LangID	1
ALP23	0
outer r	3.3
ALP22	53
D_	161.925
ALP21	29
SHOG_yobi	6576R/6535R
RAr	293.6
inner r	3.5
GRS rpm	2200
D_b	154
D_a	141
DE_	140.732
SLR	40.4
Prod_Type3	TRBSR_ID_A
BETA_	1
ALPHA_	14.942
SDM_	123.623
DA1	19.211
DA2	16.578
hidYobi	6576/6535
Y1	1.5
B_	55.1
Oil rpm	3000

hidTable	ecat_NSTPRI
Y0	0.82
inner ra	3.5
outer rb	3.3
C0	480
CUP	1.67
e	0.4
DA_	17.9
BET21	3
BET22	45
BET23	0
Z_	19
C_	42.862
yobi	6576/6535
KBRG	3161
CONE	3.74
DI_	106.055