

NSK RSF-4892E4 cylindrical roller bearings

Browse NSK RSF-4892E4 cylindrical roller bearings Categories in the Manufacturers Online Free. 107.95 mm da including .

da	107.95 mm
Da	214.998 mm
Ca	67.793 mm
A1	120.65 mm
A2	190.5 mm
S	4.763 mm
ba	53.181 mm
H	257.175 mm
H1	133.35 mm
H2	53.975 mm
J min.	336.55 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	22.225 mm
R1	79.375 mm
R2	30.163 mm
RG	1/2 NPT
PG	1/4 NPT
h	46.831 mm
Housing	SAFS 524
Bearing	22224 EK
Adapter sleeve assembly	SNW 24×4.1/4

Stabilizing ring	SR-24-20
Labyrinth ring	2 x LOR 114
End plug (suffix Y)	EPR 14
Bearing limiting speed	3800 r/min
P60°	249 kN
P90°	149 kN
P120°	94.3 kN
P150°	87.2 kN
P180°	107 kN
Pa	20.7 kN
Mass pillow block	62.6 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	0.75 in
Initial grease fill	379.89 g