

NSK STF800RV1014g cylindrical roller bearings

are a few brands you will find 92.075×148.43×28.575 Size (mm) 148,43 Outer Diameter (mm) in our inventory. Find NSK STF800RV1014g cylindrical roller bearings to see what's in stock!

Size (mm)	92.075×148.43×28.575
Bore Diameter (mm)	92,075
Outer Diameter (mm)	148,43
Width (mm)	28,575
d	92,075 mm
D	148,43 mm
T	28,575 mm
B	28,971 mm
C	21,433 mm
ra1 max.	3 mm
a	31,8 mm
r min.	3,5 mm
r1 min.	3 mm
Da	134 mm
db	101 mm
ra max.	3,5 mm
da	107 mm
Db	142 mm
Weight	1,843 Kg
Basic dynamic load rating (C)	140 kN
Basic static load rating (C0)	218 kN

(Grease) Lubrication Speed	2200 r/min
(Oil) Lubrication Speed	3000 r/min
Calculation factor (e)	0,49
Calculation factor (Y0)	0,67
LangID	1
ALP23	0
outer r	3
ALP22	20
D_	148.43
ALP21	36
SHOG_yobi	42362R/42584R
RAr	223
inner r	3.5
GRS rpm	2200
D_b	142
D_a	134
DE_	133.298
SLR	20
Prod_Type3	TRBSR_ID_A
BETA_	1
ALPHA_	18.167
SDM_	121.584
DA1	12.323
DA2	11.222
hidYobi	42362/42584
Y1	1.2
B_	28.971
Oil rpm	3000
hidTable	ecat_NSTPRI

Y0	0.67
inner ra	3.5
outer rb	3
C0	218
CUP	0.553
e	0.49
DA_	11.775
BET21	3
BET22	10
BET23	0
Z_	26
C_	21.433
yobi	42362/42584
KBRG	3161
CONE	1.29
DI_	110.205