

NSK ZA-57BWKH04E2-Y-01 E tapered roller bearings

What is the 80 mm d best place to 14 mm B buy NSK ZA-57BWKH04E2-Y-01 E tapered roller bearings online? Manufacturing 125 mm D Service .

d	80 mm
D	125 mm
B	14 mm
rs min	0.6 mm
Radial clearance class	C4
Mass	0.6 kg
Dynamic load, C	25.4 kN
Static load, C0	25.1 kN
Fatigue limit load, Cu	1.13 kN
f0	16.4
Nlim (oil)	6,200 rpm
Nlim (grease)	5,300 rpm
Min operating temperature, Tmin	-60 °C
Characteristic cage frequency, FTF	0.46 Hz
Characteristic rolling element frequency, BSF	11.66 Hz
Characteristic outer ring frequency, BPF0	9.15 Hz
Characteristic inner ring frequency, BRFI	10.85 Hz
da min	84 mm
Da max	121 mm

ra max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.63
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C4-Extra Loose
Inch – Metric	Metric
Long Description	80MM Bore; 125MM Outside Diameter; 14MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fi
Other Features	Deep Groove Radial
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	1.3904
Outer Race Width	0.551 Inch 14 Millimeter
Bore	3.15 Inch 80 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	4.921 Inch 125 Millimeter