

# NTN 24032BK30 spherical roller bearings

YOU'LL FIND AN EXTENSIVE 45.796 mm Ca SELECTION OF NTN 24032BK30 spherical roller bearings 73.025 mm da FOR SALE.

da	73.025 mm
Da	150 mm
Ca	45.796 mm
A1	88.9 mm
A2	127 mm
ba	31.75 mm
H	182.166 mm
H1	95.25 mm
H2	31.75 mm
J min.	250.825 mm
J max.	279.4 mm
J1	53.975 mm
L	330.2 mm
N1	19.05 mm
R1	53.975 mm
R2	22.225 mm
RG	3/8 NPT
PG	1/8 NPT
h	36.513 mm
Housing	FSAF 517
Bearing	1217 K
Adapter sleeve assembly	SNW 17×2.7/8
Stabilizing ring	2 x SR-1517

Labyrinth ring	2 x LOR 52
End plug (suffix Y)	EPR 9
Bearing limiting speed	5600 r/min
P60°	61.4 kN
P90°	36.9 kN
P120°	23.1 kN
P150°	20.9 kN
P180°	25.4 kN
Pa	7.12 kN
Mass pillow block	16.5 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.625 in
Initial grease fill	218.29 g