

NTN 29875/29820D+A tapered roller bearings

Offer High Quality Brand NTN 29875/29820D+A tapered roller bearings .Contact Us 147.637 mm da 359.999 mm Da Online to 129.794 mm Ca Get Best Quote.

da	147.637 mm
Da	359.999 mm
Ca	129.794 mm
A1	203.2 mm
A2	352.425 mm
S	4.763 mm
ba	91.281 mm
H	422.275 mm
H1	209.55 mm
H2	85.725 mm
J min.	571.5 mm
J max.	635 mm
J1	127 mm
L	749.3 mm
N1	34.925 mm
R1	122.237 mm
R2	42.862 mm
RG	1 NPT
PG	1/4 NPT
h	69.85 mm
Housing	SAF 634
Bearing	22334 CCK/W33

Adapter sleeve assembly	SNW 134×5.13/16
Stabilizing ring	SR-40-34
Taconite seal	TER 138
End plug (suffix Y)	EPR 18
Max. speed for Taconite seal	520 r/min
P60°	364 kN
P90°	218 kN
P120°	136 kN
P150°	120 kN
P180°	145 kN
Pa	60.9 kN
Mass pillow block	213 kg
Cap bolt	4 x 7/8-9 UNC
Cap bolt recommended tightening torque	271.2 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.25 in
Initial grease fill	2154.6 g