

# NTN 32256 tapered roller bearings

offers a NTN 32256 tapered roller bearings selection of Genuine at 22,225 mm d Wholesale Prices. We are a NTN 32256 tapered roller bearings Certified 22,225 Bore Diameter (mm) Parts Retailer

Bore Diameter (mm)	22,225
d	22,225 mm
s1	19.8 mm
A	36 mm
A1	22 mm
B	34,1 mm
G	10 mm
H	70 mm
H1	36.5 mm
H2	16 mm
J	102 mm
L	130 mm
N	19,5 mm
N1	11.5 mm
Weight	0,81 Kg
Basic dynamic load rating (C)	14 kN
Basic static load rating (C0)	7,8 kN
Fatigue load limit (Pu)	0,335
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A

Weight / Kilogram	0.82
EAN	7316577755568
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/8 Inch
Relubricatable	Yes
Insert Part Number	YAR 205-014-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch – Metric	Inch
Other Features	Single Row   Standard Duty   Wide Inner Race   Y Bearing   Has Flinger
Long Description	2 Bolt Pillow Block; 7/8" Bore; 1-7/16" Base to Center Height; Set Screw Mount; Ball Beari
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SY 7/8 TF
Weight / LBS	1.8
Bolt Spacing Maximum	4.344 Inch   110.338Millimeter
Actual Bolt Center to Center	0 Inch   0Millimeter

Nominal Bolt Center to Center	4.1 Inch   105 Millimeter
Bolt Spacing Minimum	3.688 Inch   93.675 Millimeter
Length Thru Bore	1.344 Inch   34.13 Millimeter
Bore	0.875 Inch   22.225 Millimeter
Base to Center Height	1.438 Inch   36.525 Millimeter
Housing material	Cast iron
A5	20.5 mm
B4	5 mm
J max.	110 mm
J min.	94 mm
RG	1/4-28 UNF
R1	2 mm
Rα	45 °
DN	6.5 mm
SWN	7 mm
GN	1/4-28 SAE-LT
J6	120 mm
J7	13 mm
N4	4 mm
Basic dynamic load rating C	14 kN
Basic static load rating C0	7.8 kN
Fatigue load limit Pu	0.335 kN
Limiting speed	7000 r/min
Mass bearing unit	0.75 kg
Thread grub screw G2	1/4-28 UNF
Hexagonal key size for grub screw N	3.175 mm
Recommended tightening torque for grub screw	4 N·m

Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in
Housing	SY 505 M
Bearing	YAR 205-014-2F
End cover	ECY 205