

# NTN 323126 tapered roller bearings

100% Authentic. NTN 323126 tapered roller bearings 105x225x49 Size (mm) Highest Quality. Certified 225 Outer Diameter (mm) Supplier.

|                               |                  |
|-------------------------------|------------------|
| Size (mm)                     | 105x225x49       |
| Bore Diameter (mm)            | 105              |
| Outer Diameter (mm)           | 225              |
| Width (mm)                    | 49               |
| d                             | 105 mm           |
| D                             | 225 mm           |
| B                             | 49 mm            |
| C                             | 49 mm            |
| Angle ( $\alpha$ )            | 30 °             |
| a                             | 23.1 mm          |
| r min.                        | 3 mm             |
| r1 min.                       | 1.1 mm           |
| 2B                            | 98 mm            |
| da min.                       | 112 mm           |
| Da max.                       | 218 mm           |
| ra max.                       | 1 mm             |
| Weight                        | 9.34 Kg          |
| Basic dynamic load rating (C) | 355 kN           |
| Basic static load rating (C0) | 410 kN           |
| (Grease) Lubrication Speed    | 2100 r/min       |
| Bore Type                     | Cylindrical Bore |
| Enclosure                     | Open             |

|                         |           |
|-------------------------|-----------|
| Configuration           | Duplex    |
| Bore Size               | 105 mm    |
| Outside Diameter        | 225 mm    |
| Width                   | 49 mm     |
| Fillet Radius/Chamfer   | 3 mm      |
| r1                      | 1.1 mm    |
| Dynamic Load Rating     | 355,000 N |
| Static Load Rating      | 410,000 N |
| Limiting Speed – Grease | 2,100 rpm |
| Limiting Speed – Oil    | 2,800 rpm |
| da1 (min)               | 119 mm    |
| da2 (min)               | 112 mm    |
| Da1 (max)               | 211 mm    |
| Da2 (max)               | 218 mm    |
| ra (max)                | 2.5 mm    |
| ra1 (max)               | 1 mm      |