

# NTN 323136E1 tapered roller bearings

What are 0.0 Inventory the dimensions of a NTN 323136E1 tapered roller bearings? REXNORD Manufacturer Name Manufacturing Service . Get Your Free, Instant Quote

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 1.634  |
| EAN                       | 0698210702137  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 3  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 3 Bolt Round Flange Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 3/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 2100U  |
| Seals                     | Heavy Contact  |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | With Pilot   |
| Inch – Metric             | Inch   |
| Long Description          | 3 Bolt Round Flange Block; 1" Bore; 4.2" Bolt Circle; 3-37/64" Bolt Spacing; 1 Piece |

|                                       |  |
|---------------------------------------|--|
| Other Features                        | Double Row   Single Collar  <br>With Set Screw |
| UNSPSC                                | 31171501                                       |
| Harmonized Tariff Code                | 8483.20.40.80                                  |
| Noun                                  | Bearing  |
| Keyword String                        | Flanged  |
| Manufacturer Item Number              | MB2100S  |
| Manufacturer Internal Number          | 6870213  |
| Weight / LBS                          | 4.2  |
| Cartridge Pilot Diameter              | 3 Inch   76.2 Millimeter                       |
| d                                     | 1 Inch   25.4 Millimeter                       |
| Cartridge Pilot Depth                 | 0.188 Inch   4.775 Millimeter                  |
| Bolt Spacing                          | 3.578 Inch   90.881<br>Millimeter              |
| Nominal Bolt Circle Diameter<br>Round | 4.2 Inch   106.7 Millimeter                    |
| D                                     | 2.563 Inch   65.09 Millimeter                  |