

NTN 32940XUE1 tapered roller bearings

NTN 32940XUE1 tapered roller bearings Product Brochures , 120 Bore Diameter (mm) Manufacturing Service . 120x45x29 Size (mm) Get Your Free.

Size (mm)	120x45x29
Bore Diameter (mm)	120
Outer Diameter (mm)	45
Width (mm)	29
d	45 mm
D	120 mm
B	29 mm
d1	68.91 mm
D1	95.85 mm
r1,2 – min.	2 mm
da – min.	58 mm
Da – max.	107 mm
ra – max.	2 mm
Basic dynamic load rating – C	76.1 kN
Basic static load rating – C0	45 kN
Fatigue load limit – Pu	1.9 kN
Reference speed	13000 r/min
Limiting speed	8500 r/min
Calculation factor – kr	0.035
Calculation factor – f0	12.1
Inventory	0.0
Manufacturer Name	SKF

Minimum Buy Quantity	N/A
Weight / Kilogram	1.581
EAN	7316576621154
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	45MM Bore; 120MM Outside Diameter; 29MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6409
Weight / LBS	3.48
Bore	1.772 Inch 45 Millimeter
Outer Race Width	1.142 Inch 29 Millimeter
Outside Diameter	4.724 Inch 120 Millimeter
bore diameter:	45 mm
static load capacity:	45 kN
outside diameter:	120 mm
precision rating:	ABEC 1 (ISO Class Normal)

overall width:	29 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	29 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	2 mm
snap ring included:	Without Snap Ring
maximum rpm:	8500 RPM
internal clearance:	C0
series:	64
dynamic load capacity:	76.1 kN
d1 ≈	68.91 mm
D1 ≈	95.85 mm
r1,2 min.	2 mm
da min.	58 mm
Da max.	107 mm
ra max.	2 mm
Basic dynamic load rating C	76.1 kN
Basic static load rating C0	45 kN
Fatigue load limit Pu	1.9 kN
Calculation factor kr	0.035
Calculation factor f0	12.1
Mass bearing	1.57 kg