

NTN 413140 tapered roller bearings

NTN 413140 tapered roller bearings Engineering Calculator , Manufacturing Service . Get Your Free. 130x180x32 Size (mm)

Size (mm)	130x180x32
Bore Diameter (mm)	130
Outer Diameter (mm)	180
Width (mm)	32
d	130 mm
D	180 mm
T	32 mm
B	32 mm
C	25 mm
a	31,4 mm
r min.	2 mm
r1 min.	1,5 mm
da min.	142 mm
Da min	168 mm
Da max.	170 mm
db max.	140 mm
Db min.	173 mm
ra max.	2 mm
rb max.	1,5 mm
Weight	2,46 Kg
Basic dynamic load rating (C)	200 kN
Basic static load rating (C0)	365 kN
(Grease) Lubrication Speed	1800 r/min

(Oil) Lubrication Speed	2400 r/min
Calculation factor (e)	0,34
Calculation factor (Y0)	0,97
LangID	1
outer r	1.5
D_	180
TC-BET22	50
TC-BET21	1
TC-BET23	0
inner r	2
mass	2.46
GRS rpm	1800
D_b	173
Cr	20400
TC-RA	390.5
DE_	167.309
T-ALP23	0
db	140
T-ALP22	30
Prod_Type3	TRBSR_MD_A
da	142
T-ALP21	25
Iso	2CC
ALPHA_	12.75
SDM_	155.392
SBRG	29
D_a2	168
hidYobi	HR32926J
Y1	1.8

D_a1	170
B_	32
hidTable	ecat_NSTPRM
Oil rpm	2400
C0r	37500
Y0	0.97
TC-SLR	23
inner ra	2
outer rb	1.5
C0	365
Sa	6
Sb	7
e	0.34
DA_	12.127
Z_	35
C_	25
yobi	HR32926J
TC-DA1	12.494
TC-DA2	11.76
KBRG	3111
DI_	143.474