

NTN 430315DU tapered roller bearings

Offer High Quality Brand NTN 430315DU tapered roller bearings .Contact 110x170x28 Size (mm) Us Online to Get Best Quote.

Size (mm)	110x170x28
Bore Diameter (mm)	110
Outer Diameter (mm)	170
Width (mm)	28
d	110 mm
D	170 mm
B	28 mm
C	28 mm
r min.	2 mm
da min.	119 mm
da max	126 mm
Da max.	161 mm
ra max.	2 mm
Weight	1,96 Kg
Basic dynamic load rating (C)	82 kN
Basic static load rating (C0)	73 kN
Reference speed	2 300 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359551068
Product Group	B00308

Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	110MM Bore; 170MM Outside Diameter; 28MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; N
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Alvania Prelubricat
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	4.32
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	1.102 Inch 28 Millimeter
Outside Diameter	6.693 Inch 170 Millimeter
Bore	4.331 Inch 110 Millimeter
bore diameter:	110 mm
precision rating:	ISO Class 0
outside diameter:	170 mm

finish/coating:	Uncoated
overall width:	28 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	28 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	28 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	2300 rpm
internal clearance:	CN
fillet radius:	2 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	4500 RPM
dynamic load capacity:	82000 N
series:	60
static load capacity:	73000 N
manufacturer product page:	Click here