

# NTN 432320U tapered roller bearings

are a few brands you will find in 6 mm d our inventory. Find NTN 432320U tapered roller bearings to see what's in stock!

d	6 mm
D	19 mm
B	6 mm
rs min	0.3 mm
Radial clearance class	CN
Mass	0.008 kg
Dynamic load, C	2.34 kN
Static load, C0	0.88 kN
Fatigue limit load, Cu	0.04 kN
f0	12.1
Nlim (grease)	34,000 rpm
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	110 °C
da min	8 mm
da max	9.5 mm
Da max	17 mm
ra max	0.3 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.008

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	6MM Bore; 19MM Outside Diameter; 6MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Fi
Other Features	Deep Groove   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C   Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Outer Race Width	0.236 Inch   6 Millimeter
Outside Diameter	0.748 Inch   19 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Bore	0.236 Inch   6 Millimeter