

NTN 4R14205 cylindrical roller bearings

Enjoy High Margins on Competitive 110 mm D 60 mm d Pricing.Great Wholesale Products at 22 mm B Low Costs.

| | |
|---|-----------|
| d | 60 mm |
| D | 110 mm |
| B | 22 mm |
| rs min | 1.5 mm |
| Radial clearance class | C3 |
| Mass | 0.78 kg |
| Dynamic load, C | 52.5 kN |
| Static load, C0 | 36 kN |
| Fatigue limit load, Cu | 1.64 kN |
| f0 | 14.3 |
| Nlim (oil) | 7,000 rpm |
| Nlim (grease) | 6,000 rpm |
| Min operating temperature, Tmin | -60 °C |
| Characteristic cage frequency, FTF | 0.41 Hz |
| Characteristic rolling element frequency, BSF | 5.26 Hz |
| Characteristic outer ring frequency, BPF0 | 4.08 Hz |
| Characteristic inner ring frequency, BRFI | 5.92 Hz |
| da min | 68 mm |
| Da max | 102 mm |
| ra max | 1.5 mm |

| | |
|---------------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.782 |
| EAN | 4547359368536 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Brass |
| Internal Clearance | C3-Loose |
| Inch – Metric | Metric |
| Long Description | 60MM Bore; 110MM Outside Diameter; 22MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fi |
| Other Features | Deep Groove Riveted Solid Cage |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer Item Number | 6212L1AC3 |
| Weight / LBS | 2.068 |
| Inner Race Width | 0 Inch 0 Millimeter |
| Outer Race Width | 0.866 Inch 22 Millimeter |

| | |
|------------------|--------------------------------|
| Outside Diameter | 4.331 Inch 110 Millimeter |
| Bore | 2.362 Inch 60 Millimeter |