

# NTN 4R4050 cylindrical roller bearings

NTN 4R4050 cylindrical roller bearings, Units and Housings CAD models N/A Minimum Buy Quantity , Manufacturing Service 0.0 Inventory ABB MOTORS AND MECHANICAL INC Manufacturer Name . Get Your Free.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC                  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 0.468  |
| EAN                       | 0782475985258                                  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Set Screw                                      |
| Housing Style             | 2 Bolt Pillow Block                            |
| Rolling Element           | Ball Bearing                                   |
| Housing Material          | Polymer  |
| Expansion / Non-expansion | Non-expansion                                  |
| Mounting Bolts            | 12 Millimeter                                  |
| Relubricatable            | Yes  |
| Insert Part Number        | INS-SC-45M-CR                                  |
| Seals                     | Single Lip Contact                             |
| Housing Configuration     | 1 Piece Solid                                  |
| Inch – Metric             | Metric   |
| Other Features            | Single Row   Normal Duty   Corrosion Resistant |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 45MM Bore; 54MM Base to Center Height; Set Screw Mount; Ball Bearing; 137.7MM M |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.40  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | P2B-SCEZ-45M-PCR   |
| Manufacturer Internal Number  | 127550   |
| Weight / LBS                  | 2.271  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| Bolt Spacing Maximum          | 5.969 Inch   151.6Millimeter   |
| B                             | 2.126 Inch   54 Millimeter   |
| d                             | 1.772 Inch   45 Millimeter   |
| Bolt Spacing Minimum          | 5.421 Inch   137.7Millimeter   |
| Nominal Bolt Center to Center | 5.7 Inch   146 Millimeter  |
| D                             | 1.72 Inch   43.7 Millimeter  |