

# NTN 4R6605 cylindrical roller bearings

What is NTN 4R6605 cylindrical roller bearings in mechanical engineering? Manufacturing Service . Upload 0.0 Inventory your CAD file for an instant. IPTCI BEARINGS Manufacturer Name

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | IPTCI BEARINGS  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 1.905   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Set Screw   |
| Housing Style             | 4 Bolt Square Flange Block  |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Nickel Coated Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 1/2 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | SUC208  |
| Seals                     | B Seal  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Metric  |
| Long Description          | 4 Bolt Square Flange Block;<br>40MM Bore; 144MM Bolt Circle;<br>102MM Bolt Spacing; 1 Piece<br>Solid; Set Scr |

|                                    |  |
|------------------------------------|--|
| Other Features                     | Single Row   Spherical   Corrosion Resistant   Stainless Steel Insert   Has Slinger   Optional Locki |
| UNSPSC                             | 31171501   |
| Harmonized Tariff Code             | 8483.20.40.40  |
| Noun                               | Bearing  |
| Keyword String                     | Flanged  |
| Manufacturer Item Number           | SUCNPF 208 40MM  |
| Weight / LBS                       | 4.2  |
| Nominal Bolt Circle Diameter Round | 5.7 Inch   144 Millimeter  |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter  |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter  |
| Bolt Spacing                       | 4 Inch   102 Millimeter  |
| d                                  | 1.575 Inch   40 Millimeter   |
| D                                  | 1.937 Inch   49.2 Millimeter   |