

# NTN 4T-15100/15250X tapered roller bearings

What are the types of NTN 4T-15100/15250X tapered roller bearings SKF Manufacturer Name ? Manufacturing Service . Get Your Free, Instant price, design 0.0 Inventory review.

|                                 |  |
|---------------------------------|--|
| Inventory                       | 0.0  |
| Manufacturer Name               | SKF  |
| Minimum Buy Quantity            | N/A  |
| Weight                          | 0  |
| Product Group                   | B04270                                     |
| Enclosure                       | Open                                       |
| Flush Ground                    | Yes  |
| Rolling Element                 | Ball Bearing                               |
| Number of Rows of Balls         | Single Row                                 |
| Precision Class                 | ABEC 1   ISO P0                            |
| Maximum Capacity / Filling Slot | No   |
| Snap Ring                       | No   |
| Cage Material                   | PEEK                                       |
| Contact Angle                   | 15 Degree                                  |
| Internal Clearance              | C0-Medium                                  |
| Number of Bearings              | 4 (1 Quadruplex Set)                       |
| Preload                         | Light                                      |
| Mounting Arrangement            | Quadruplex-Back to Back of Pairs in Tandem |
| Inch – Metric                   | Metric                                     |

|                        |  |
|------------------------|--|
| Long Description       | 70MM Bore; 110MM Outside Diameter; 80MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of B |
| Other Features         | High Speed Design  |
| UNSPSC                 | 31171531   |
| Harmonized Tariff Code | 8482.10.50.28  |
| Noun                   | Bearing  |
| Keyword String         | Angular Contact  |
| B                      | 3.15 Inch   80 Millimeter  |
| d                      | 2.756 Inch   70 Millimeter   |
| D                      | 4.331 Inch   110 Millimeter  |