

# NTN 4T-25580/25521 tapered roller bearings

Can't find what you're 0.0 Inventory looking for NTN 4T-25580/25521 tapered roller bearings ? Our expert Representatives be in contact TIMKEN Manufacturer Name with you shortly!

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 106.69   |
| EAN                       | 0883450140270  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Eccentric Collar   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 23230  |
| Seals                     | Triple Lip Viton   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   SN Style  |
| Long Description          | 4 Bolt Pillow Block; 6" Bore; 6.693" Base to Center Height; Eccentric Collar Mount; Spheri |

|                               |                                 |
|-------------------------------|---------------------------------|
| UNSPSC                        | 31171511                        |
| Harmonized Tariff Code        | 8483.20.40.80                   |
| Noun                          | Bearing                         |
| Keyword String                | Pillow Block                    |
| Weight / LBS                  | 250                             |
| Nominal Bolt Center to Center | 18.1 Inch   459.7 Millimeter    |
| B                             | 6.693 Inch   170.002 Millimeter |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter            |
| D                             | 7.56 Inch   192.024 Millimeter  |
| Bolt Spacing Maximum          | 19 Inch   482.6Millimeter       |
| d                             | 6 Inch   152.4 Millimeter       |
| Bolt Spacing Minimum          | 17.25 Inch   438.15Millimeter   |