

# NTN 4T-27880/27820 tapered roller bearings

How do I place an EMERGENCY 38,1 Bore Diameter (mm) order for a NTN 4T-27880/27820 tapered roller bearings that I want 65,088 Outer Diameter (mm) to pick 38.1×65.088×18.821 Size (mm) up at a our store?

Size (mm)	38.1×65.088×18.821
Bore Diameter (mm)	38,1
Outer Diameter (mm)	65,088
Width (mm)	18,821
d	38,1 mm
D	65,088 mm
T	18,821 mm
B	18,288 mm
C	13,97 mm
d1	52 mm
a	13.73 mm
e	0.33
Y2	1.8
Y0	0.99
Mass	0.23 kg
Dynamic load, C	43.5 kN
Rating life coefficient, A2	1.4
Static load, C0	57 kN
Fatigue limit load, Cu	7 kN
Nlim (oil)	7,400 rpm
Nlim (grease)	5,500 rpm

Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	8.22 Hz
Characteristic outer ring frequency, BPF0	9.27 Hz
Characteristic inner ring frequency, BRFI	11.73 Hz
ra max	3.94 mm
r1a max	1.3 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.248
Product Group	B04334