

# NTN 4T-389/382A tapered roller bearings

Our highly-skilled and factory-trained service experts have the resources to help you with all your NTN 4T-389/382A tapered roller bearings needs – including 0.0 Inventory routine maintenance, major repairs, warranty service, and equipment inspections.

|                           |                               |
|---------------------------|-------------------------------|
| Inventory                 | 0.0                           |
| Manufacturer Name         | TIMKEN                        |
| Minimum Buy Quantity      | N/A                           |
| Weight                    | 14.528                        |
| EAN                       | 0883450167321                 |
| Product Group             | M06288                        |
| Number of Mounting Holes  | 4                             |
| Mounting Method           | Eccentric Collar              |
| Housing Style             | 4 Bolt Round Flange Cartridge |
| Rolling Element           | Spherical Roller Bearing      |
| Housing Material          | Cast Steel                    |
| Expansion / Non-expansion | Expansion                     |
| Mounting Bolts            | 3/4 Inch                      |
| Relubricatable            | Yes                           |
| Insert Part Number        | 22218                         |
| Seals                     | Triple Lip Nitrile Rubber     |
| Housing Configuration     | 1 Piece Solid                 |
| Pilot Configuration       | With Pilot                    |
| Inch – Metric             | Inch                          |

|                                       |   |
|---------------------------------------|---|
| Long Description                      | 4 Bolt Round Flange Cartridge;<br>3-7/16" Bore; 8.6" Bolt<br>Circle; 6.1" Bolt Spacing; 1 P |
| Other Features                        | Double Row  |
| UNSPSC                                | 31171501  |
| Harmonized Tariff Code                | 8483.20.40.80   |
| Noun                                  | Bearing   |
| Keyword String                        | Flanged   |
| Weight / LBS                          | 32  |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter   |
| Cartridge Pilot Diameter              | 7.375 Inch   187.32 Millimeter  |
| Bolt Spacing                          | 6.1 Inch   154.9 Millimeter   |
| D                                     | 4.03 Inch   102.362 Millimeter  |
| d                                     | 3.438 Inch   87.325 Millimeter  |
| Nominal Bolt Circle Diameter<br>Round | 8.6 Inch   218.4 Millimeter   |