## NTN 4T-39573/39520 tapered roller bearings

Our highly-skilled and factory-trained service N/A Minimum Buy Quantity experts have 0.0 Inventory the resources to help you with all your NTN 4T-39573/39520 tapered roller bearings needs — including routine maintenance, major repairs, warranty service, and equipment inspections.

| Inventory                 | 0.0                           |
|---------------------------|-------------------------------|
| Manufacturer Name         | TIMKEN                        |
| Minimum Buy Quantity      | N/A                           |
| Weight                    | 32.688                        |
| EAN                       | 0883450167659                 |
| Product Group             | M06288                        |
| Number of Mounting Holes  | 6                             |
| Mounting Method           | Eccentric Collar              |
| Housing Style             | 6 Bolt Round Flange Cartridge |
| Rolling Element           | Spherical Roller Bearing      |
| Housing Material          | Cast Steel                    |
| Expansion / Non-expansion | Expansion                     |
| Mounting Bolts            | 3/4 Inch                      |
| Relubricatable            | Yes                           |
| Insert Part Number        | 22222                         |
| Seals                     | Double Lip Nitrile Rubber     |
| Housing Configuration     | 1 Piece Solid                 |
| Pilot Configuration       | With Pilot                    |
| Inch — Metric             | Metric                        |

| Long Description                      | 6 Bolt Round Flange Cartridge;<br>110MM Bore; 300MM Bolt Circle;<br>149.225MM Bolt Spacing; 1<br>Piece Solid; |
|---------------------------------------|---|
| Other Features                        | Double Row  |
| UNSPSC                                | 31171501  |
| Harmonized Tariff Code                | 8483.20.40.80   |
| Noun                                  | Bearing   |
| Keyword String                        | Flanged   |
| Weight / LBS                          | 72  |
| Bolt Spacing                          | 5.875 Inch   149.225<br>Millimeter  |
| D                                     | 5.53 Inch   140.462 Millimeter  |
| d                                     | 4.331 Inch   110 Millimeter   |
| Cartridge Pilot Diameter              | 10.25 Inch   260.35 Millimeter  |
| Nominal Bolt Circle Diameter<br>Round | 11.8 Inch   300 Millimeter  |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter   |