

NTN 4T-39575/39520 tapered roller bearings

We work closely with our NTN 4T-39575/39520 tapered roller bearings manufacturing partners to 80 Bore Diameter (mm) bring the best value to customers. 80x40x56.3 Size (mm) 40 Outer Diameter (mm)

Size (mm)	80x40x56.3
Bore Diameter (mm)	80
Outer Diameter (mm)	40
Width (mm)	56,3
d	40 mm
D	80 mm
B1	56.3 mm
C	21 mm
d1	51.8 mm
d2	56.5 mm
B	42.8 mm
B4	6.75 mm
r1,2 – min.	1 mm
s1	34.9 mm
Basic dynamic load rating – C	30.7 kN
Basic static load rating – C0	19 kN
Fatigue load limit – Pu	0.8 kN
Limiting speed with shaft tolerance h6	2800 r/min
Calculation factor – f0	14
Mass bearing	0.67 kg
Thread – G2	M10x1

Hexagonal key size for grub screw – H	5 mm
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.7
EAN	7316570355062
Product Group	M06110
d1 ≈	51.8 mm
r1,2 min.	1 mm
Basic dynamic load rating C	30.7 kN
Basic static load rating C0	19 kN
Fatigue load limit Pu	0.8 kN
Limiting speed1)	2800 r/min
Calculation factor f0	14
Mass complete bearing	0.71 kg
Thread grub screw G2	M10x1
Hexagonal key size for grub screw N	5 mm
Recommended tightening torque for grub screw	16.5 N·m
Rubber seating ring	RIS 208 A