

NTN 4T-418/414 tapered roller bearings

Enjoy 0.0 Inventory N/A Minimum Buy Quantity High Margins on Competitive Pricing.Great Wholesale SKF Manufacturer Name Products at Low Costs.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	66.009
EAN	7316576602795
Product Group	B04311
Internal Clearance	C3-Loose
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AH3148 A0H3148 (Specify bore)
Withdrawal Nut	HM52T
Inch – Metric	Metric
Long Description	240MM Tapered Bore; 400MM Outside Diameter; 128MM Width; C3-Loose Clearance; Adapter Mount; Double R

Other Features	Order adapter or withdrawal sleeve or nut separately. Others may be available
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Weight / LBS	145.395
B	5.039 Inch 128 Millimeter
d	9.449 Inch 240 Millimeter
Adapter Part Number	SNP3148 H3148 (Specify bore) Inch H3148 (Specify bore) Millimeter
D	15.748 Inch 400 Millimeter
bore diameter:	240 mm
maximum rpm:	1600 RPM
outside diameter:	400 mm
operating temperature range:	Maximum of +390 °F
overall width:	128 mm
cage material:	Steel
bore type:	Tapered 1:12
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C3
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	128 mm

dynamic load capacity:	2080 kN
fillet radius:	3 mm
static load capacity:	3200 kN
series:	231