

NTN 4T-46790/46720 tapered roller bearings

We work closely with our NTN 4T-46790/46720 tapered roller bearings manufacturing 0.0 Inventory N/A Minimum Buy Quantity partners to bring the best value to customers.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	68.74
EAN	0013992039187
Product Group	B04144
Number of Mounting Holes	4
Mounting Method	Clamp Collar
Housing Style	4 Bolt Pillow Block
Rolling Element	Cylindrical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	24 Millimeter
Relubricatable	Yes
Insert Part Number	MSE407BX
Seals	Triple Lip Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Inch
Other Features	Single Row Medium Duty With Support Wide Inner Ring Axial Float
UNSPSC	31171511

Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Weight / LBS	151.4
D	3.937 Inch 100 Millimeter
d	4.438 Inch 112.725 Millimeter
Nominal Bolt Center to Center	17.7 Inch 450 Millimeter
Bolt Spacing Minimum	0 Inch 0Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
B	6.378 Inch 162 Millimeter
Actual Bolt Center to Center	17.7 Inch 450Millimeter
Shaft Size	4-7/16 in
Seal Type	Aluminium Triple Labyrinth
Bearing Type	Split Cylindrical Expansion Type
Support Type	Four-Bolt Plummer Block
Series Type	Medium Series
Pillow/Plummer Block Style	Split Cylindrical Housed Unit – SAFQ
Bolt Size	4 x 7/8
Bearing UPC	013992032584
Dimension H	6 in
Dimension H2	13.1 in
Dimension J1	16 in
Dimension J2	14-1/2 in
Dimension K	3-1/4 in
Dimension L	18-3/8 in
Dimension M	5-1/8 in
Housing Width	6.4 in

Cr – Dynamic Load Rating	102130 lbf
Cor – Static Load Rating	133135 lbf
Maximum Speed	1820 rpm
Note	This product line was formerly known as “Revolvo”