

# NTN 4T-529X/522 tapered roller bearings

NTN 4T-529X/522 tapered roller bearings Industries and Applications ? We sell discount 15.88×28.575×1.9837 Size (mm) 15,88 Bore Diameter (mm) online as well as cheap machinery parts.

Size (mm)	15.88×28.575×1.9837
Bore Diameter (mm)	15,88
Outer Diameter (mm)	28,575
Width (mm)	1,9837
d	15,88 mm
D	28,575 mm
T	1,9837 mm
Ea	25,908 mm
Eb	18,03 mm
Weight	0,003 Kg
Basic dynamic load rating (C)	9,79 kN
Basic static load rating (C0)	30,38 kN
Inventory	136.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.004
EAN	0605790213823
Product Group	B04144
Rolling Element	Needle Roller Bearing
Self Aligning	No
Component Description	Roller Assembly Only

Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1   ISO P0
Other Features	Single Row   Two Piece Cage
Long Description	5/8" Bore 1; 5/8" Bore 2; 1-1/8" Outside Diameter; 5/64" Height; Needle Roller B
Inch – Metric	Inch
UNSPSC	31171500
Harmonized Tariff Code	8482.99.25.40
Noun	Roller Assembly
Keyword String	Thrust Needle
Manufacturer Item Number	NTA-1018
Weight / LBS	0.007
Outside Diameter	1.125 Inch   28.575 Millimeter
Overall Height with Aligning Washer	0 Inch   0 Millimeter
Bore 2	0.625 Inch   15.875 Millimeter
Height	0.078 Inch   1.981 Millimeter
Bore 1	0.625 Inch   15.875 Millimeter
Bearing No.	NTA-1018
Dc1	15.88
Dc	28.575
Dw	1.9837
Ca	9.79
C0a	30.38
Cu	2.85
Limiting speeds(min-1)	15000

(Refer.)Mass(kg)	0.003
Washer designation	TRA-1018
d1	28.58
h(max)	0.81
h(min)	0.76
S(max)	15.88
S(min)	15.80
H	29.36
(Refer.)Washer mass(kg)	0.003