

# NTN 4T-577/572 tapered roller bearings

YOU'LL 15 mm d FIND AN 15 Bore Diameter (mm) EXTENSIVE SELECTION OF NTN 4T-577/572 tapered roller bearings FOR SALE.

Bore Diameter (mm)	15
d	15 mm
Da	49 mm
A1	2 mm
B1	28,6 mm
G	6 mm
H	81 mm
H1	– mm
J	63 mm
L	–
N	7,1 mm
T	24,1 mm
A2	7 mm
Weight	0,24 Kg
Basic dynamic load rating (C)	9,56 kN
Basic static load rating (C0)	4,75 kN
Housing material	Pressed steel
B	19.1 mm
B4	4.75 mm
Da min.	44 mm
s1	22.1 mm
Basic dynamic load rating C	9.56 kN
Basic static load rating C0	4.75 kN

Fatigue load limit Pu	0.2 kN
Permissible radial housing load max.	2.5 kN
Mass unit	0.25 kg
Thread grub screw G2	M6x0.75
Hexagonal key size for grub screw N	3 mm
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	6 mm
Recommended diameter for attachment bolts, inch G	0.25 in
Bearing	YET 203/15
Housing	PF 40