

NTN 4T-71437/71751D+A tapered roller bearings

Browse NTN 4T-71437/71751D+A tapered roller bearings 0.0 Inventory Categories N/A Minimum Buy Quantity in SKF Manufacturer Name the Manufacturers Online Free. including .

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	97.688
EAN	7316571680408
Product Group	M06288
inside diameter:	170 mm, 6.9375 in
housing material:	Cast Iron
base to bore centerline:	190 mm
compatible bearing type:	Spherical Roller
overall length:	560 mm
finish/coating:	Uncoated
overall height:	375 mm
compatible bearing series/part number:	23138CCK/W33, C3138 K
overall width:	260 mm
bolt center-to-center length:	18.9 in
mounting:	Four-Bolt Base
base width:	8.27 in
housing construction:	Split Pillow Block
series:	SNL
compatible bore diameter:	170 mm, 6.9375 in
standards met:	ISO/DIS 185 Grade 200

Bearing (basic designation)	22330
Lock nut	KM 30
Lock washer	MB 30
Locating ring	2 x FRB 8/320
da	150 mm
db	170 mm
d2	300 mm
Ca	124 mm
Da	320 mm
A	260 mm
A1	210 mm
ATS	270 mm
ATK	353 mm
H	375 mm
H1	190 mm
H2	80 mm
J	480 mm
J1	120 mm
L	560 mm
N	34 mm
N1	28 mm
s	10 mm
ba min.	85 mm
ba max.	112 mm
bb	80 mm
bc	117.5 mm
J6	520 mm
N4 max.	20 mm
Labyrinth seal	2 x TS 38

Taconite seal	2 x TK 38
End cover	ETS 38
P0°	2200 kN
P55°	2700 kN
P90°	1300 kN
P120°	1000 kN
P150°	880 kN
P180°	1100 kN
Pa	710 kN
Q120°	1800 kN
Q150°	1040 kN
Q180°	900 kN
Mass housing	97.5 kg
Cap bolt, size	M 24×150
Cap bolt, rec. tightening torque	350 N·m
Appropriate attachment bolt, size G	24 mm
Appropriate attachment bolt, rec. tightening torque	665 N·m
Eye bolt, size	2 x M 20
Initial grease fill, 20%	1.2 kg
Initial grease fill, 40%	1.8 kg
Adapter sleeve	HA 3138