

NTN 4T-95525/95925 tapered roller bearings

100% Authentic. NTN 4T-95525/95925 tapered roller bearings 20x42x25 Size (mm) Highest Quality. Certified Supplier.

Size (mm)	20x42x25
Bore Diameter (mm)	20
Outer Diameter (mm)	42
Width (mm)	25
d	20 mm
D	42 mm
B	25 mm
C	16 mm
α	17 °
dk	35.5 mm
b	3.1 mm
b1	3.1 mm
M	2 mm
r1 – min.	0.3 mm
r2 – min.	0.6 mm
da – min.	22.7 mm
da – max.	25.2 mm
Da – min.	36.9 mm
Da – max.	39.2 mm
ra – max.	0.3 mm
rb – max.	0.6 mm
Basic dynamic load rating – C	72 kN
Basic static load rating – C0	240 kN

Specific factor dynamic load – K	150 N/mm ²
Specific factor static load – K ₀	500 N/mm ²
Constant – K _M	330
Lubricant	Maintenance free – greased for life
Design (sliding contact surface combination)	Steel/steel
Sealing solution	Triple-lip seals
α	17 °
r ₁ min.	0.3 mm
r ₂ min.	0.6 mm
d _a min.	22.7 mm
d _a max.	25.2 mm
D _a min.	36.9 mm
D _a max.	39.2 mm
r _a max.	0.3 mm
r _b max.	0.6 mm
Basic dynamic load rating C	72 kN
Basic static load rating C ₀	240 kN
Specific dynamic load factor K	150 N/mm ²
Specific static load factor K ₀	500 N/mm ²
Material constant K _M	330
Mass plain bearing	0.16 kg