

# NTN 5302S angular contact ball bearings

100% Authentic. 30 to 180 °F operating temperature range: NTN 5302S angular contact ball bearings Highest Quality. Certified Supplier. Tapped Base mounting: 1.1875 in d

|                              |                               |
|------------------------------|-------------------------------|
| mounting:                    | Tapped Base                   |
| operating temperature range: | 30 to 180 °F                  |
| d                            | 1.1875 in                     |
| D                            | 3.0000 in                     |
| bore type:                   | Round                         |
| maximum rpm:                 | 2900 rpm                      |
| base to bore centerline:     | 1.6875 in                     |
| bolt size:                   | 7/16 in                       |
| duty type:                   | Normal Duty                   |
| tap thread size:             | 7/16-24                       |
| housing material:            | Black Polyamide               |
| lubrication type:            | Lubrication Fitting           |
| locking device:              | Set Screw                     |
| series:                      | UCPA                          |
| seal type:                   | Single Lip Contact            |
| cap type:                    | Yellow Protective Cap         |
| expansion type:              | Non-Expansion Bearing (Fixed) |
| end cap type:                | No End Cap                    |
| overall length:              | 3.8594 in                     |
| bearing material:            | 52100 Chrome Bearing Steel    |
| overall height:              | 3.3438 in                     |
| manufacturer catalog number: | 73206B-U                      |

|                                |                 |
|--------------------------------|-----------------|
| finish/coating:                | Black Polyamide |
| manufacturer upc number:       | 787405281387    |
| B                              | 1.6406 in       |
| Weight                         | 1.15 lbs        |
| maximum operating temperature: | Max 180 °       |