

NTN 562922 thrust ball bearings

Advance NTN 562922 thrust ball bearings 65 mm d is your source for quality and accessories. shop online for home delivery 33 mm B or pick up in one of our 10000 .

d	65 mm
D	140 mm
B	33 mm
rs min	2.1 mm
Radial clearance class	C4
Mass	2.08 kg
Dynamic load, C	92.5 kN
Static load, C0	60 kN
Fatigue limit load, Cu	2.7 kN
f0	13.2
Nlim (oil)	5,800 rpm
Nlim (grease)	4,900 rpm
Min operating temperature, Tmin	-60 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.07 Hz
Characteristic outer ring frequency, BPF0	3.07 Hz
Characteristic inner ring frequency, BRFI	4.93 Hz
da min	76 mm
Da max	129 mm
ra max	2 mm

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	2.082
EAN	4547359398120
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C4-Extra Loose
Inch – Metric	Metric
Long Description	65MM Bore; 140MM Outside Diameter; 33MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6313C4
Weight / LBS	4.59
Outer Race Width	1.299 Inch 33 Millimeter
Outside Diameter	5.512 Inch 140 Millimeter

Bore	2.559 Inch 65 Millimeter
bore diameter:	65 mm
finish/coating:	Uncoated
outside diameter:	140 mm
bearing material:	High Carbon Chrome Steel
overall width:	33 mm
cage material:	Steel
bore type:	Round
inner ring width:	33 mm
closure type:	Open
outer ring width:	33 mm
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	4900 rpm
snap ring included:	Without Snap Ring
maximum rpm (oil):	5800 rpm
internal clearance:	C4
fillet radius:	2.1 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	5800 RPM
dynamic load capacity:	92500 N
series:	63
static load capacity:	60000 N
manufacturer product page:	Click here
precision rating:	Class 0