

NTN 5S-2LA-BNS009CLLBG/GNP42 angular contact ball bearings

What are the dimensions of 0.0 Inventory a NTN 5S-2LA-BNS009CLLBG/GNP42 angular contact ball bearings? Manufacturing Service . Get Your Free, Instant Quote

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.856
EAN	7316571114255
Product Group	B04144
Roller Surface Profile	Crowned
Profile	Stud Type
Thread Size	M30X1.5
Stud Profile	Standard Stud
Enclosure	Sealed
Rolling Element	Cylindrical Roller Bearing – Double Row
Relubricatable	Yes
Hex Socket	Yes
Inch – Metric	Metric
Other Features	Full Complement Labyrinth Seal
Long Description	80MM Roller Diameter; 35MM Roller Width; Crowned Roller Surface; Stud Type; 30MM Stud Diameter; M30X
UNSPSC	31171530

Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Keyword String	Cam Follower
Manufacturer Item Number	NUKR 80 A
Weight / LBS	3.527
Roller Width	1.378 Inch 35 Millimeter
Stud Diameter	1.181 Inch 30 Millimeter
Roller Diameter	3.15 Inch 80 Millimeter
roller diameter:	80 mm
operating temperature range:	Maximum of +280 °F
roller width:	35 mm
radial dynamic load capacity:	69.3 kN
stud diameter:	30 mm
radial static load capacity:	86.5 kN
stud length:	63 mm
maximum rpm:	1900 rpm
roller shape:	Crowned
lubrication hole location:	Head, Stud Side, Stud End
roller material:	Steel
finish/coating:	Uncoated
bearing element:	Cylindrical Rollers
standards met:	ANSI/ABMA Standard 18.1, ISO 7063
closure type:	Sealed
series:	NUKR
head type:	Hex
manufacturer catalog:	Click here
hex size:	8 mm
manufacturer upc number:	7316571114255

thread size:	M30 x 1.5 mm
D	80 mm
d	30 mm
B	100 mm
C	35 mm
B1	63 mm
B2	15 mm
C1	1 mm
d1	47 mm
G	M 30×1.5
G1	32 mm
M	8 mm
M1	4 mm
SW	14 mm
r1,2 min.	1.1 mm
Basic dynamic load rating C	69.3 kN
Basic static load rating C0	86.5 kN
Fatigue load limit Pu	10.8 kN
Maximum dynamic radial loads Fr max.	48 kN
Maximum static radial loads F0r max.	69.5 kN
Limiting speed	1900 r/min
Mass cam follower	1.6 kg
Recommended tightening torque	450 N·m
Grease fitting	NIP A3x9.5
Hexagonal nut	M 30×1.5
Lubrication adapter	AP 14