

NTN 5S-7911UCG/GNP42 angular contact ball bearings

NTN 5S-7911UCG/GNP42 angular contact ball bearings SEARCH – Whether it's agriculture Cylindrical Bore Bore Type or construction equipment Single Shield with Snap Ring Enclosure your working Single Row Configuration on, Has the you need.

| | |
|----------------------------|------------------------------|
| Enclosure | Single Shield with Snap Ring |
| Bore Type | Cylindrical Bore |
| Configuration | Single Row |
| Weight | 0.567 kg |
| d | 120 mm |
| D | 150 mm |
| B | 16 mm |
| Fillet Radius/Chamfer | 1 mm |
| r1 | 0.5 mm |
| Snap Ring Width | 1.7 mm |
| Snap Ring Outside Diameter | 155.7 mm |
| D1 (max) | 147.6 mm |
| a (max) | 2.5 mm |
| b (min) | 1.9 mm |
| Dynamic Load Rating | 28,300 N |
| Static Load Rating | 31,500 N |
| Limiting Speed – Grease | 4,000 rpm |
| Limiting Speed – Oil | 4,800 rpm |
| Factor fo | 16.0 |
| Radial Clearance | 0.015 to 0.041 mm |
| da (min) | 125 mm |

| | |
|----------|--------|
| Da (max) | 145 mm |
| Dx (min) | 157 mm |
| ra (max) | 1 mm |
| Cy (max) | 3.9 mm |