

# NTN 6016LLU deep groove ball bearings

With over 10170 full-service stores, our 0.0 Inventory NTN 6016LLU deep groove ball bearings inventory is extensive and our parts are priced right. within 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

|                                 |                 |
|---------------------------------|-----------------|
| Inventory                       | 0.0             |
| Manufacturer Name               | TIMKEN          |
| Minimum Buy Quantity            | N/A             |
| Weight                          | 0.11 Kg         |
| EAN                             | 0087796294820   |
| Product Group                   | B00308          |
| Enclosure                       | Open            |
| Precision Class                 | ABEC 1   ISO P0 |
| Maximum Capacity / Filling Slot | No              |
| Rolling Element                 | Ball Bearing    |
| Snap Ring                       | No              |
| Internal Special Features       | No              |
| Cage Material                   | Steel           |
| Internal Clearance              | C0-Medium       |
| Inch – Metric                   | Metric          |
| UNSPSC                          | 31171504        |
| Harmonized Tariff Code          | 8482.10.50.68   |
| Noun                            | Bearing         |
| Keyword String                  | Ball            |
| Weight / LBS                    | 0.249           |

|                          |                            |
|--------------------------|----------------------------|
| Outer Race Width         | 0.512 Inch   13 Millimeter |
| Inner Race Width         | 0.512 Inch   13 Millimeter |
| d                        | 1.181 Inch   30 Millimeter |
| D                        | 2.165 Inch   55 Millimeter |
| Clearance                | C0 (Normal)                |
| Bore Size d              | 30 mm                      |
| Features                 | Open                       |
| Outside Diameter D       | 55.000 mm                  |
| Outside Ring Width B     | 13.000 mm                  |
| Radius Rs min            | 1.000 mm                   |
| Cr – Dynamic Load Rating | 13.2 kN                    |
| C0r – Static Load Rating | 8.3 kN                     |
| Grease Reference Speed   | 12000 rpm                  |
| Oil Reference Speed      | 18000 rpm                  |