NTN 6303LLBNR deep groove ball bearings

We -20 to +220 °F operating temperature range: work closely with 4-15/16 in D our NTN 6303LLBNR deep groove ball bearings 2-3/16 in d manufacturing partners to bring the best value to customers.

d2-3/16 inoperating temperature range:-20 to +220 °FD4-15/16 inradial dynamic load capacity:9752 lbhousing width:1-19/32 inradial static load capacity:6601 lbinner ring width:2-3/16 inmaximum rpm:1400 RPMhousing material:Cast Ironseal type:Feltlocking device:Set Screwlubrication type:Lubrication Fittingexpansion type:Non-Expansion Bearing (Fixed)bearing material:Chrome Steelfinish/coating:Uncoated		
D4-15/16 inradial dynamic load capacity:9752 lbhousing width:1-19/32 inradial static load capacity:6601 lbinner ring width:2-3/16 inmaximum rpm:1400 RPMhousing material:Cast Ironseal type:Feltlocking device:Set Screwlubrication type:Lubrication Fittingexpansion type:Non-Expansion Bearing (Fixed)bearing material:Chrome Steelfinish/coating:Uncoated	d	2-3/16 in
radial dynamic load capacity:9752 lbhousing width:1-19/32 inradial static load capacity:6601 lbinner ring width:2-3/16 inmaximum rpm:1400 RPMhousing material:Cast Ironseal type:Feltlocking device:Set Screwlubrication type:Lubrication Fittingexpansion type:Non-Expansion Bearing (Fixed)bearing material:Chrome Steelfinish/coating:Uncoated	operating temperature range:	-20 to +220 °F
housing width:1-19/32 inradial static load capacity:6601 lbinner ring width:2-3/16 inmaximum rpm:1400 RPMhousing material:Cast Ironseal type:Feltlocking device:Set Screwlubrication type:Lubrication Fittingexpansion type:Non-Expansion Bearing (Fixed)bearing material:Chrome Steel	D	4-15/16 in
radial static load capacity: 6601 lb inner ring width: 2-3/16 in maximum rpm: 1400 RPM housing material: Cast Iron seal type: Felt locking device: Set Screw lubrication type: Lubrication Fitting expansion type: Non-Expansion Bearing (Fixed) bearing material: Chrome Steel finish/coating: Uncoated	radial dynamic load capacity:	9752 lb
inner ring width: 2-3/16 in maximum rpm: 1400 RPM housing material: Cast Iron seal type: Felt locking device: Set Screw lubrication type: Lubrication Fitting expansion type: Non-Expansion Bearing (Fixed) bearing material: Chrome Steel finish/coating: Uncoated	housing width:	1-19/32 in
maximum rpm: 1400 RPM housing material: Cast Iron seal type: Felt locking device: Set Screw lubrication type: Lubrication Fitting expansion type: Non-Expansion Bearing (Fixed) bearing material: Chrome Steel finish/coating: Uncoated	radial static load capacity:	6601 lb
housing material:Cast Ironseal type:Feltlocking device:Set Screwlubrication type:Lubrication Fittingexpansion type:Non-Expansion Bearing (Fixed)bearing material:Chrome Steelfinish/coating:Uncoated	inner ring width:	2-3/16 in
seal type:Feltlocking device:Set Screwlubrication type:Lubrication Fittingexpansion type:Non-Expansion Bearing (Fixed)bearing material:Chrome Steelfinish/coating:Uncoated	maximum rpm:	1400 RPM
locking device:Set Screwlubrication type:Lubrication Fittingexpansion type:Non-Expansion Bearing (Fixed)bearing material:Chrome Steelfinish/coating:Uncoated	housing material:	Cast Iron
lubrication type:Lubrication Fittingexpansion type:Non-Expansion Bearing (Fixed)bearing material:Chrome Steelfinish/coating:Uncoated	seal type:	Felt
expansion type: Non-Expansion Bearing (Fixed) bearing material: Chrome Steel finish/coating: Uncoated	locking device:	Set Screw
bearing material: Chrome Steel finish/coating: Uncoated	lubrication type:	Lubrication Fitting
finish/coating: Uncoated	expansion type:	Non-Expansion Bearing (Fixed)
	bearing material:	Chrome Steel
series: SC	finish/coating:	Uncoated
	series:	SC