

NTN 6314LU deep groove ball bearings

With over 10170 full-service 210 Bore Diameter (mm) stores, our NTN 6314LU deep groove ball bearings 210x140x53 Size (mm) inventory is extensive and our parts are priced right. within 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

| | |
|-------------------------------|------------|
| Size (mm) | 210x140x53 |
| Bore Diameter (mm) | 210 |
| Outer Diameter (mm) | 140 |
| Width (mm) | 53 |
| d | 140 mm |
| D | 210 mm |
| B | 53 mm |
| d2 | 155 mm |
| D1 | 197 mm |
| b | 8.3 mm |
| K | 4.5 mm |
| r1,2 – min. | 2 mm |
| da – min. | 145 mm |
| da – max. | 155 mm |
| Da – max. | 201 mm |
| ra – max. | 2 mm |
| Basic dynamic load rating – C | 485 kN |
| Basic static load rating – C0 | 680 kN |
| Fatigue load limit – Pu | 68 kN |
| Limiting speed | 700 r/min |

| | |
|-----------------------------|---------------|
| Calculation factor – e | 0.2 |
| Calculation factor – Y1 | 3.4 |
| Calculation factor – Y2 | 5 |
| Calculation factor – Y0 | 3.2 |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 6.145 |
| EAN | 7316574276578 |
| Product Group | B04311 |
| d2 ≈ | 155 mm |
| D1 ≈ | 197 mm |
| r1,2 min. | 2 mm |
| Da max. | 201 mm |
| ra max. | 2 mm |
| Basic dynamic load rating C | 485 kN |
| Basic static load rating C0 | 680 kN |
| Fatigue load limit Pu | 68 kN |
| Calculation factor e | 0.2 |
| Calculation factor Y1 | 3.4 |
| Calculation factor Y2 | 5 |
| Calculation factor Y0 | 3.2 |
| Mass bearing | 6.35 kg |