

NTN 6319LLB deep groove ball bearings

What are the dimensions of a NTN 6319LLB deep groove ball bearings? Manufacturing Service . Get Your Free, 22x12x10 Size (mm) Instant Quote

Size (mm)	22x12x10
Bore Diameter (mm)	22
Outer Diameter (mm)	12
Width (mm)	10
d	12 mm
D	22 mm
B	10 mm
C	7 mm
α	10 °
dk	18 mm
r1 – min.	0.3 mm
r2 – min.	0.3 mm
da – min.	13.8 mm
da – max.	15 mm
Da – min.	17.1 mm
Da – max.	20.4 mm
ra – max.	0.3 mm
rb – max.	0.3 mm
Basic dynamic load rating – C	10.8 kN
Basic static load rating – C0	54 kN
Specific factor dinamic load – K	100 N/mm ²
Specific factor static load – K0	500 N/mm ²

Constant – KM	330
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.022
EAN	7316576609206
Product Group	B04264
Self Aligning	Yes
Rolling Element	Spherical Plain
Material – Outer Member	Steel
Material – Ball	Steel
Material – Liner	Not Applicable
Relubricatable	Yes
Enclosure	Open
Other Features	2 Piece Side Lubrication Only
Long Description	12MM Bore; 7MM Housing Width; 22MM Outside Diameter; Spherical Plain; Steel Outer Member; Steel Ball
Inch – Metric	Metric
UNSPSC	31171515
Harmonized Tariff Code	8483.30.80.70
Noun	Bearing
Keyword 3	Spherical
Keyword String	Plain Spherical Radial
Manufacturer Item Number	GE 12 E
Weight / LBS	0.037
Bore	0.472 Inch 12 Millimeter

Overall Width	0.394 Inch 10 Millimeter
Outside Diameter	0.866 Inch 22 Millimeter
Housing Width	0.276 Inch 7 Millimeter
bore diameter:	12 mm
inner ring material:	Chrome Steel
outside diameter:	22 mm
outer ring width:	7 mm
misalignment angle:	10 °
radial static load capacity:	54 kN
inner ring width:	10 mm
radial dynamic load capacity:	10.8 kN
bearing type:	Radial
operating temperature range:	-50 to +200 °C °F
lubrication type:	Requires Lubrication
overall width:	10 mm
closure type:	Open
manufacturer upc number:	7316576609206
outer ring material:	Chrome Steel
Lubricant	Regular relubrication – grease
Design (sliding contact surface combination)	Steel/steel
Sealing solution	–
α	10 °
r1 min.	0.3 mm
r2 min.	0.3 mm
da min.	13.8 mm
da max.	15 mm
Da min.	17.1 mm

Da max.	20.4 mm
ra max.	0.3 mm
rb max.	0.3 mm
Basic dynamic load rating C	10.8 kN
Basic static load rating C0	54 kN
Specific dynamic load factor K	100 N/mm ²
Specific static load factor K0	500 N/mm ²
Material constant KM	330
Mass plain bearing	0.016 kg