

NTN 6805LLU deep groove ball bearings

What is the 150 Outer Diameter (mm) best place 110x150x40 Size (mm) to buy NTN 6805LLU deep groove ball bearings online? Manufacturing Service .

Size (mm)	110x150x40
Bore Diameter (mm)	110
Outer Diameter (mm)	150
Width (mm)	40
d	110 mm
D	150 mm
B	40 mm
D1	135.8 mm
F	123 mm
b	5.5 mm
K	3 mm
r1,2 – min.	1.1 mm
r3,4 – min.	0.6 mm
s	1.1 mm
da – min.	116 mm
da – max.	121 mm
Da – max.	143.5 mm
ra – max.	1 mm
dn	124 mm
Basic dynamic load rating – C	132 kN
Basic static load rating – C0	270 kN
Fatigue load limit – Pu	30 kN

Limiting speed for grease lubrication	5300 r/min
Limiting speed for oil lubrication	6000 mm/min
Gref	17 cm
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.216
EAN	7316577014818
Product Group	B04270
Bore Profile	Tapered
Cage Material	Brass
Precision Class	Special Precision
Number of Rows of Rollers	Double Row
Separable	Inner Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C1-Tight
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Plain Inner Ring 3 Rib Outer Ring High Precision Bearing Modified Internal Design Cage on Ou

Long Description	110MM Bore; Tapered Bore Profile; 150MM Outside Diameter; 40MM Width; Brass Cage Material; Special
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NNU 4922 BK/SPW33
Weight / LBS	4.882
Bore	4.331 Inch 110 Millimeter
Width	1.575 Inch 40 Millimeter
Outside Diameter	5.906 Inch 150 Millimeter
bore diameter:	110 mm
precision rating:	Not Rated
outside diameter:	150 mm
maximum rpm:	6000 RPM
overall width:	40 mm
bearing material:	Chrome Steel
flanges:	(3) Outer Ring
cage material:	Brass
bore type:	Straight
finish/coating:	Uncoated
number of rows:	2
closure type:	Open
internal clearance:	C1
outer ring width:	40 mm
dynamic load capacity:	132 kN

fillet radius:	1.1 mm
static load capacity:	270 kN
series:	NNU49
r _{1,2} min.	1.1 mm
r _{3,4} min.	0.6 mm
s max.	1.1 mm
d _a min.	116 mm
d _a max.	121 mm
D _a max.	143.5 mm
Basic dynamic load rating C	132 kN
Basic static load rating C ₀	270 kN
Fatigue load limit P _u	30 kN
Attainable speed for grease lubrication	5300 r/min
Attainable speed for oil-air lubrication	6000 r/min
Reference grease quantity G _{ref}	17 cm ³
Static radial stiffness (guideline value)	3130 N/μm
Mass bearing	2.05 kg