

NTN 7220CDB/GNP5 angular contact ball bearings

What are 260x170x28 Size (mm) the types of NTN 7220CDB/GNP5 angular contact ball bearings ? Manufacturing Service . Get Your Free, Instant price, design review.

Size (mm)	260x170x28
Bore Diameter (mm)	260
Outer Diameter (mm)	170
Width (mm)	28
d	170 mm
D	260 mm
B	28 mm
d1	200.25 mm
D1	228.7 mm
r1,2 – min.	1.5 mm
da – min.	177 mm
Da – max.	253 mm
ra – max.	1.5 mm
Basic dynamic load rating – C	119 kN
Basic static load rating – C0	129 kN
Fatigue load limit – Pu	3.8 kN
Reference speed	5300 r/min
Limiting speed	3200 r/min
Calculation factor – kr	0.02
Calculation factor – f0	16.4
Inventory	0.0
Manufacturer Name	SKF

Minimum Buy Quantity	N/A
Weight / Kilogram	5.013
EAN	7316577004673
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	170MM Bore; 260MM Outside Diameter; 28MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; N
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	16034
Weight / LBS	11.042
Bore	6.693 Inch 170 Millimeter
Outer Race Width	1.102 Inch 28 Millimeter
Outside Diameter	10.236 Inch 260 Millimeter
bore diameter:	170 mm
static load capacity:	129 kN
outside diameter:	260 mm
precision rating:	Not Rated

overall width:	28 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	28 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	1.5 mm
snap ring included:	Without Snap Ring
maximum rpm:	3200 RPM
internal clearance:	C0
series:	16
dynamic load capacity:	119 kN
d1 ≈	200.25 mm
D1 ≈	228.7 mm
r1,2 min.	1.5 mm
da min.	177 mm
Da max.	253 mm
ra max.	1.5 mm
Basic dynamic load rating C	119 kN
Basic static load rating C0	129 kN
Fatigue load limit Pu	3.75 kN
Calculation factor kr	0.02
Calculation factor f0	16.4
Mass bearing	5.02 kg