

NTN 7334DBC3P5 angular contact ball bearings

offers a NTN 7334DBC3P5 angular contact ball bearings selection of Genuine at Wholesale Prices. We are 35 Outer Diameter (mm) a NTN 7334DBC3P5 angular contact ball bearings Certified 72x35x17 Size (mm) Parts Retailer

Size (mm)	72x35x17
Bore Diameter (mm)	72
Outer Diameter (mm)	35
Width (mm)	17
d	35 mm
D	72 mm
B	17 mm
D1	60.2 mm
F	44 mm
r1,2 – min.	1.1 mm
r3,4 – min.	0.6 mm
s	1.3 mm
da – min.	39.8 mm
da – max.	42.2 mm
db – min.	46 mm
Da – max.	65.1 mm
ra – max.	1 mm
rb – max.	0.6 mm
Basic dynamic load rating – C	56 kN
Basic static load rating – C0	48 kN
Fatigue load limit – Pu	6.1 kN

Reference speed	11000 r/min
Limiting speed	12000 r/min
Calculation factor – kr	0.15
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.352
EAN	7316576621680
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	35MM Bore; Straight Bore Profile; 72MM Outside Diameter; 17MM Width; Brass Cage Material; RBEC 1
UNSPSC	31171547

Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NU 207 ECM
Weight / LBS	0.776
Outside Diameter	2.835 Inch 72 Millimeter
Width	0.669 Inch 17 Millimeter
Bore	1.378 Inch 35 Millimeter
bore diameter:	35 mm
precision rating:	RBEC 1 (ISO Class Normal)
outside diameter:	72 mm
maximum rpm:	12000 RPM
overall width:	17 mm
bearing material:	Steel
flanges:	(2) Outer Ring
cage material:	Brass
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C0
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
ring separation:	Separable Ring
outer ring width:	17 mm
operating temperature range:	Maximum of +300 °F
fillet radius:	1 mm
dynamic load capacity:	56 kN
series:	NU2
static load capacity:	48 kN

D1 ≈	60.2 mm
r1,2 min.	1.1 mm
r3,4 min.	0.6 mm
s max.	1.3 mm
da min.	39.8 mm
da max.	42.2 mm
db min.	46 mm
Da max.	65.1 mm
ra max.	1 mm
rb max.	0.6 mm
Basic dynamic load rating C	56 kN
Basic static load rating C0	48 kN
Fatigue load limit Pu	6.1 kN
Calculation factor kr	0.15
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	0.34 kg
Angle ring	HJ 207 EC