

NTN 7906UCG/GNP4 angular contact ball bearings

Can't find what you're looking 77.8 mm Ca for NTN 7906UCG/GNP4 angular contact ball bearings ? Our expert Representatives be in contact 127 mm da with you shortly!

| | |
|-------------------------------|----------------|
| da | 127 mm |
| Da | 250 mm |
| Ca | 77.8 mm |
| A1 | 149.225 mm |
| A2 | 193.675 mm |
| S | 4.763 mm |
| ba | 61.119 mm |
| H | 298.45 mm |
| H1 | 152.4 mm |
| H2 | 60.325 mm |
| L | 511.175 mm |
| R1 | 87.313 mm |
| R2 | 38.1 mm |
| RG | 3/4 NPT |
| PG | 1/4 NPT |
| h | 51.594 mm |
| Housing | SSAFS 528 |
| Bearing | 22228 CCK/W33 |
| Adapter sleeve assembly | SNW 28×5 |
| Stabilizing ring | SR-28-0 |
| Labyrinth ring | 2 x LOR 123 |
| PosiTrac Plus contact element | 2 x B10724-122 |

| | |
|--|----------------|
| End plug (suffix Y) | EPR 27 |
| Max. speed for PosiTrac Plus seal | 1150 r/min |
| P60° | 301 kN |
| P90° | 180 kN |
| P120° | 116 kN |
| P150° | 105 kN |
| P180° | 127 kN |
| Pa | 28.5 kN |
| Mass pillow block | 94.3 kg |
| Cap bolt | 3/4-10 UNC |
| Cap bolt recommended tightening torque | 515.2 N·m |
| Cap bolt, SAE grade | 8 |
| Eye bolt | 2 x 3/8-16 UNC |
| Initial grease fill | 481.95 g |