

NTN 81228 thrust ball bearings

Various types 168.275 mm db and sizes to accommodate 150 mm da your NTN 81228 thrust ball bearings requirements.

| | |
|---------|------------|
| da | 150 mm |
| db | 168.275 mm |
| dc | 146.05 mm |
| Da | 269.999 mm |
| Ca | 82.804 mm |
| A1 | 158.75 mm |
| A2 | 215.9 mm |
| S | 4.763 mm |
| ba | 65.088 mm |
| H | 320.675 mm |
| H1 | 160.325 mm |
| H2 | 63.5 mm |
| J min. | 431.8 mm |
| J max. | 463.55 mm |
| J1 | 95.25 mm |
| L | 539.75 mm |
| N1 | 28.575 mm |
| R1 | 95.25 mm |
| R2 | 39.688 mm |
| RG | 3/4 NPT |
| PG | 1/4 NPT |
| h | 50.8 mm |
| Housing | SAF 230 |

| | |
|---|----------------|
| Bearing | 22230 CC/W33 |
| Lock nut | AN 30 |
| Lock washer | W 30 |
| Stabilizing ring | SR-30-0 |
| Labyrinth ring (db shaft position) | LOR 151 |
| PosiTrac Plus contact element (db shaft position) | B10724-151 |
| Labyrinth ring (dc shaft position) | LOR 134 |
| PosiTrac Plus contact element (dc shaft position) | B10724-134 |
| End plug (suffix Y) | EPR 17 |
| Max. speed for PosiTrac Plus seal | 850 r/min |
| P60° | 230 kN |
| P90° | 138 kN |
| P120° | 87.2 kN |
| P150° | 80.1 kN |
| P180° | 96.1 kN |
| Pa | 62.3 kN |
| Mass pillow block | 82.3 kg |
| Cap bolt | 4 x 3/4-10 UNC |
| Cap bolt recommended tightening torque | 203.4 N·m |
| Cap bolt, SAE grade | 5 |
| Eye bolt | 2 x 3/8-16 UNC |
| Appropriate attachment bolt size G | 1 in |
| Initial grease fill | 623.7 g |