

NTN AC-6001LLB deep groove ball bearings

LET OUR NTN AC-6001LLB deep groove ball bearings EXPERTS GET YOU THE PARTS YOU NEED. 35×34.5×13 Size (mm)

Size (mm)	35×34.5×13
Bore Diameter (mm)	35
Outer Diameter (mm)	34,5
Width (mm)	13
d	35 mm
A	34.5 mm
A1	13 mm
A3 – H14	3.2 mm
A5	22 mm
B1	51.1 mm
Da – H11	106.4 mm
Db1	87 mm
Db2	95 mm
J	92 mm
L	118 mm
H	14 mm
s1	32.3 mm
T	53.3 mm
J6	106 mm
J7	29 mm
N4	4 mm
DN	6.5 mm
SWN	7 mm

GN – 1/4-28 SAE-LT	1/428 SAELT
RG – 1/4-28 UNF	1/428 UNF
R1	22.5 mm
Basic dynamic load rating – C	25.5 kN
Basic static load rating – C0	15.3 kN
Fatigue load limit – Pu	0.655 kN
Limiting speed	5300 r/min
Mass bearing unit	1.4 kg
Thread – G2	M10x1
Hexagonal key size for grub screw – H	5 mm
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.445
Product Group	M06110
Housing material	Cast iron
Da	106.4 mm
A3	3.2 mm
N	14 mm
RG	1/4-28 UNF
GN	1/4-28 SAE-LT
Basic dynamic load rating C	25.5 kN
Basic static load rating C0	15.3 kN
Fatigue load limit Pu	0.655 kN
Thread grub screw G2	M10x1
Hexagonal key size for grub screw N	5 mm
Recommended tightening torque for grub screw	16.5 N·m
Recommended diameter for attachment bolts, mm G	12 mm

Recommended diameter for attachment bolts, inch G	0.5 in
Housing	FY 507 M
Bearing	YEL 207-2F
End cover	ECY 207