

NTN CRD-4019 tapered roller bearings

We Provide Extensive NTN CRD-4019 tapered roller bearings Selection 120x260x55 Size (mm) And Competitive Wholesale 260 Outer Diameter (mm) Pricing.

Size (mm)	120x260x55
Bore Diameter (mm)	120
Outer Diameter (mm)	260
Width (mm)	55
d	120 mm
D	260 mm
B	55 mm
C	55 mm
Angle (α)	30 °
a	27.3 mm
r min.	3 mm
r1 min.	1.1 mm
da min.	134 mm
Da max.	246 mm
ra max.	2.5 mm
Weight	14.2 Kg
Basic dynamic load rating (C)	260 kN
Basic static load rating (C0)	169 kN
(Grease) Lubrication Speed	2200 r/min
Configuration	Single Row
Enclosure	Open
Bore Type	Cylindrical Bore

Bore Size	120 mm
Outside Diameter	260 mm
Width	55 mm
Fillet Radius/Chamfer	3 mm
r1	1.1 mm
Dynamic Load Rating	260,000 N
Static Load Rating	169,000 N
Limiting Speed – Grease	2,200 rpm
Limiting Speed – Oil	3,000 rpm
da1 (min)	134 mm
da2 (min)	127 mm
Da1 (max)	246 mm
Da2 (max)	253 mm
ra (max)	2.5 mm
ra1 (max)	1 mm