

NTN CRD-6135 tapered roller bearings

We work closely with our NTN CRD-6135 tapered roller bearings manufacturing partners to bring the best value to customers.

| | |
|---|-------------|
| d | 15 mm |
| D | 60 mm |
| H | 25 mm |
| d ₂ | 26.7 mm |
| D ₂ | 36.1 mm |
| H ₁ | 17 mm |
| r _{1,2} min. | 0.3 mm |
| r _{3,4} min. | 0.6 mm |
| a | 62 mm |
| J | 46 mm |
| N | 6.8 mm |
| d _a min. | 20 mm |
| D _a max. | 35 mm |
| r _a max. | 0.3 mm |
| Basic dynamic load rating C | 20.4 kN |
| Basic static load rating C ₀ | 33.5 kN |
| Fatigue load limit P _u | 1.3 kN |
| Attainable speed | 7700 r/min |
| Preload | 650 N |
| Frictional moment | 0.1 N·m |
| Static axial stiffness | 430 N/μm |
| Static moment stiffness | 65 N·m/mrad |

| | |
|--|---------|
| Mass bearing | 0.42 kg |
| Required attachment bolt size (DIN 912) | M6 |
| Number of attachment bolts | 5 |
| Angle between holes in outer ring (Pitch) α | 60 ° |