

NTN CRD-8040 tapered roller bearings

NTN CRD-8040 tapered roller bearings, Units and Housings CAD models , 20 mm d 20 Bore Diameter (mm) Manufacturing Service . Get Your Free.

Bore Diameter (mm)	20
d	20 mm
U	34 mm
Thread (Q)	Rp1/8
d3	33 mm
A	20 mm
A1	11 mm
B1	31 mm
H1	35 mm
H2	92 mm
J	89,5 mm
N	11,5 mm
A2	10,5 mm
Weight	0,56 Kg
Basic dynamic load rating (C)	12,8 kN
Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.671
EAN	4012802791051
Product Group	M06110
Number of Mounting Holes	3

Mounting Method	Eccentric Collar
Housing Style	3 Bolt Triangular Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	11.5 Millimeter
Relubricatable	Yes
Insert Part Number	GRAE20NPPB
Seals	Double Lip Contact
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Metric
Long Description	3 Bolt Triangular Flange Block; 20MM Bore; 90MM Bolt Circle; 78.5MM Bolt Spacing; 1 Piece Solid; Ecc
Other Features	Single Row With Set Screw
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	PCFTR20
Weight / LBS	1.235
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
Nominal Bolt Circle Diameter Round	3.5 Inch 90 Millimeter
Length Thru Bore	1.22 Inch 31 Millimeter
Bolt Spacing	3.1 Inch 78.5 Millimeter

Bore	0.787 Inch 20 Millimeter
------	----------------------------