

# NTN CRD-9704 tapered roller bearings

What are the dimensions of Dry 1.65, Periodic Lubrication 3.25 N/mm<sup>2</sup> x m/s maximum pv value: a NTN CRD-9704 tapered roller bearings? 29 mm D Manufacturing Service . Get Your Free, 16 mm d Instant Quote

|                              |  |
|------------------------------|--|
| d                            | 16 mm  |
| maximum pv value:            | Dry 1.65, Periodic Lubrication 3.25 N/mm <sup>2</sup> x m/s        |
| D                            | 29 mm  |
| maximum p value:             | 29 N/mm <sup>2</sup> ;Static 150 N/mm <sup>2</sup>                 |
| overall length:              | 12 mm  |
| maximum v value:             | Dry 0.50;Periodic lubrication 1.0 m/s                              |
| material specification:      | 500SP1 SL1   |
| sleeve bearing type:         | Flanged Bearing  |
| standards met:               | RoHS   |
| flange width:                | 3 mm   |
| series:                      | SPF  |
| bearing material:            | OILES 500SP1 SL1 High-strength Brass with Embedded Solid Lubricant |
| additional details:          | Lead Free  |
| operating temperature range: | Periodic Lubrication -40 to +302 °F, Dry -40 to +572               |