

NTN CRI-2654 tapered roller bearings

What are the dimensions of a NTN CRI-2654 tapered roller bearings? Manufacturing Service . Get Your Free, Instant 140x80x26 Size (mm) Quote 140 Bore Diameter (mm)

Size (mm)	140x80x26
Bore Diameter (mm)	140
Outer Diameter (mm)	80
Width (mm)	26
d	80 mm
D	140 mm
B	26 mm
d1	101.4 mm
D2	126.5 mm
r1,2 – min.	2 mm
da – min.	91 mm
da – max.	100.9 mm
Da – max.	129 mm
ra – max.	2 mm
Basic dynamic load rating – C	72.8 kN
Basic static load rating – C0	55 kN
Fatigue load limit – Pu	2.2 kN
Limiting speed	3000 r/min
Calculation factor – kr	0.025
Calculation factor – f0	15
Inventory	0.0
Manufacturer Name	SKF

Minimum Buy Quantity	N/A
Weight / Kilogram	1.48
EAN	7316570959338
Product Group	B00308
Enclosure	1 Seal
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	80MM Bore; 140MM Outside Diameter; 26MM Outer Race Diameter; 1 Seal; Ball Bearing; ABEC 1 ISO P0;
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6216-RS1
Weight / LBS	3.26
Bore	3.15 Inch 80 Millimeter
Outside Diameter	5.512 Inch 140 Millimeter
Outer Race Width	1.024 Inch 26 Millimeter
d1 ≈	101.4 mm
D2 ≈	126.5 mm
r1,2 min.	2 mm

da min.	91 mm
da max.	100.9 mm
Da max.	129 mm
ra max.	2 mm
Basic dynamic load rating C	72.8 kN
Basic static load rating C ₀	55 kN
Fatigue load limit P _u	2.2 kN
Calculation factor k _r	0.025
Calculation factor f ₀	15
Mass bearing	1.51 kg