

# NTN CR0-13708 tapered roller bearings

Our highly-skilled 0.0 Inventory and factory-trained service TIMKEN Manufacturer Name experts have the resources to help you with all your NTN CR0-13708 tapered roller bearings needs – including routine maintenance, major repairs, warranty service, and equipment inspections.

|                           |                           |
|---------------------------|---------------------------|
| Inventory                 | 0.0                       |
| Manufacturer Name         | TIMKEN                    |
| Minimum Buy Quantity      | N/A                       |
| Weight                    | 17.706                    |
| EAN                       | 0883450082426             |
| Product Group             | M06288                    |
| Number of Mounting Holes  | 2                         |
| Mounting Method           | Eccentric Collar          |
| Housing Style             | 2 Bolt Pillow Block       |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel                |
| Expansion / Non-expansion | Non-expansion             |
| Mounting Bolts            | 7/8 Inch                  |
| Relubricatable            | Yes                       |
| Insert Part Number        | 22218                     |
| Seals                     | Double Lip Nitrile Rubber |
| Housing Configuration     | 1 Piece Solid             |
| Inch – Metric             | Inch                      |
| Other Features            | Double Row                |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 3-1/4" Bore; 3-3/4" Base to Center Height; Eccentric Collar Mount; Sp |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | QMP18J304SB  |
| Weight / LBS                  | 45   |
| Bolt Spacing Minimum          | 9.375 Inch   238.125Millimeter   |
| Bolt Spacing Maximum          | 11.25 Inch   285.75Millimeter  |
| D                             | 4.03 Inch   102.362 Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| d                             | 3.25 Inch   82.55 Millimeter   |
| Nominal Bolt Center to Center | 10.3 Inch   260.5 Millimeter   |
| B                             | 3.75 Inch   95.25 Millimeter   |